




D REX USER GUIDE

NOTE: Failure to fully engage crampon before use can damage product.

Spark R&D will not be held liable for product damage due to user error.

Read all instructions before beginning!

Steps 1 & 2 : Claw Mounts




1. Flip the climbing blocks on the crampon to the flat position. Slide crampon from right to left into the mounting claws on the tech toe piece.



2. Slide crampon ALL the way to the left until it hits the stop position. Rotate the crampon down until it lays flat on the board half.

Step 3 : Climbing Blocks & Wires



3. As the slope steepens, use the climbing wires together with the climbing blocks on the crampon. The climbing blocks push the crampon teeth into the snow, maintaining traction when the wires are used. Climbing blocks flip up to the stacked position for use with both short and tall wire heights. Forward stride releases boot pressure allowing the crampon to glide freely over the snow.

Now, get out and enjoy 4-wheel drive for your splitboard!



MADE IN THE USA

D REX CRAMPON

For splitboard hardboot touring

User Guide

Recommended for use with Spark & Phantom Tech Toes. Also compatible with Dynafit Speed Radical, Speed Turn, and Low Tech toe pieces.

SIZING	BOARD WAIST	CRAMPON INSIDE WIDTH
REGULAR	less than 26cm	13.8cm
WIDE	26cm or more	14.8cm